

# Easy Washing Automatic Gummy Depositing Line, Jelly Candy Machine 35-55 Stroke/Min

## Specifications :

|               |  |
|---------------|--|
| Payment Terms | L/C T/T Western Union                        |
| Keyword       | advance gummy production line, Gummy Machine |

## Detail Introduction :

### Automatic Gummy Depositing Line

## Product Description



**Automatic Gummy Depositing Line** is a part of the Gummy Machine, SINOFUDE automatic gummy depositing line design with sanitary and easy washing structure for Gummy candy with CBD or THC or Vitamin and Minerals. Etc functional products. Automatic gummy depositing line is ideal

equipment that can produce good quality gummies with the saving of both the manpower and the space occupied. Optional with Touch screen, SERVO and PLC for Automatic operation, one shot system can make one color, two color or multi-color, center filled Gummy candy also available just change the manifold and nozzles. The cooling tunnel includes automatic Chain type/Air Knife/Brush de-molding system as option.

The automatic gummy depositing line complete line was designed according to pharmaceutical machine standard, higher level sanitary structure design and fabrication, all stainless steel materials are SUS304 and SUS316L in the line and it can be equipped with UL certified or CE certified components for CE or UL certificated and FDA proved.



### **Automatic Gummy Depositing Line FLOW CHART:**

Syrup making? mixing?with gelatin or pectin with CBD or THC or Vitamin and Minerals??Stirring and holding? transporting? depositing ? cooling ? de-moulding ?following disposalà Glazing or sugar coatingà packing



| Model                 | CLM80Q-A          | CLM150-A         | CLM300-A    | CLM600-A    | CLM1000-A   |
|-----------------------|-------------------|------------------|-------------|-------------|-------------|
| Capacity ( kg/h)      | 60~80             | 150              | 300         | 600         | 1000        |
| Speed (n/min)         | Depend            | 35~55 stroke/min |             |             |             |
| Candy weight (g):     | As per candy size |                  |             |             |             |
| Electric power (kW)   | 19                | 12               | 18          | 36          | 68          |
| Chilling (option)     | Depend            | 8HP              | 12HP        | 16HP        | 30HP        |
| Compressed air        | 0.6m3/min         | 0.5m3/min        | 0.8m3/min   | 1.0m3/min   | 1.2m3/min   |
| C-Air pressure        | 0.4-0.6 Mpa       | 0.4-0.6 Mpa      | 0.4-0.6 Mpa | 0.4-0.6 Mpa | 0.4-0.6 Mpa |
| Conditions            |                   |                  |             |             |             |
| 1.Room temperature(?) | 20~25C            | 20~25C           | 20~25C      | 20~25C      | 20~25C      |
| 2.Humidity (%)        | 45~55%            | 45~55%           | 45~55%      | 45~55%      | 45~55%      |
| Machine Length (m)    | 10m               | 15m              | 15m         | 18m         | 22m         |
| Gross weight (Kgs)    | 2000              | 5000             | 6000        | 9000        | 12000       |